

M A T E R I A L S A F E T Y D A T A S H E E T      Rev. 03B

For Coating, Resins, and Related Materials NPCA 1-84  
 Manufacturer's Name                      Emergency Telephone No.  
 BENJAMIN MOORE & CO.                      800-424-9300 (CHEMTREC)  
 51 CHESTNUT RIDGE RD  
 MONTVALE, NJ 07645

Date Prepared    Last Rev Date    Information Telephone No.  
 01-19-01          12-15-97                      201-573-9600

For the most up-to-date MSDS information  
 please visit our website [www.benjaminmoore.com/msds/go.html](http://www.benjaminmoore.com/msds/go.html)

SECTION I - PRODUCT ID

\*\* HMIS CODE \*\*

PRODUCT\*: 405, n405                      HEALTH: 1  
                   CLASS: WATER THINNED PAINT                      FLAMMABILITY: 0  
                   NAME: MOORE'S LATEX GLAZING LIQUID                      REACTIVITY: 0  
                   COLOR: ALL                      PERSONAL PROT:

\*\* SARA TITLE 312 \*\*

ACUTE: N    CHRONIC: N    FIRE: N    PRESSURE: N    REACTIVITY: N  
 For a complete description of HMIS and an explanation of the PERSONAL PROT:  
 code, see Section XX.  
 \*NOTE: In the PRODUCT code a little n can be any capital letter of the  
 alphabet except P or Q.

SECTION II    HAZARDOUS INGREDIENTS

INGREDIENT	HAZ	SARA	MAX %	CAS #	TLV	PEL	STEL	CEIL	MM Hg
Nepheline Syenite	Y	N	13.4	037244-96-5	10 MG/M3	5 MG/M3	N/E	N/E	N/A

NOTE: This product contains no reported or suspected carcinogens  
 Note: This product contains pigments which may become a dust nuisance when  
 removed by abrasive blasting, sanding, or grinding.  
 This product may contain small amounts of materials known to the State of  
 California to cause cancer and reproductive harm.

SECTION III    PHYSICAL DATA

BOILING RANGE: N/A    WT/GALLON: 9.4 to 9.4    %VOL BY VOLUME: 76.2 to 76.2  
 EVAPORATION RATE: SLOWER THAN ETHER    VAPOR DENSITY: HEAVIER THAN AIR

SECTION IV    FIRE AND EXPLOSION HAZARD DATA

D.O.T. FLAMMABILITY CLASS.: NOT REGULATED    FLASH POINT: > 250 F PMCC  
 LEL: Not Applicable  
 EXTINGUISHING MEDIA: FOAM    CO2    DRY CHEMICAL    WATER FOG  
 UNUSUAL FIRE AND EXPLOSION HAZARDS:  
 Toxic gases may form when product burns.  
 Closed containers may burst if exposed to extreme heat or fire.  
 SPECIAL FIRE FIGHTING PROCEDURES:  
 Cool exposed containers with water. Use self-contained breathing apparatus.

SECTION V    HEALTH HAZARD DATA

## EFFECTS OF OVEREXPOSURE - ACUTE:

Inhalation - Irritation of the respiratory tract.

Contact - Causes eye irritation.

Ingestion of large amounts could cause serious injury.

## EFFECTS OF OVEREXPOSURE - CHRONIC:

None Known

## MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE:

None expected when used in accordance with Safe Handling and Use Information (Section VIII).

Inhalation - Irritating to respiratory tract.

PRIMARY ROUTE(S) OF ENTRY: DERMAL INHALATION INGESTION

## EMERGENCY AND FIRST AID PROCEDURES :

Inhalation - Remove to fresh air. Get medical help for any breathing difficulty.

Eye Contact - Flush thoroughly with water. Call physician.

Skin Contact - Wash with soap and water.

Ingestion - Drink 1 or 2 glasses of water to dilute.

DO NOT induce vomiting. Call physician.

-----  
SECTION VI REACTIVITY DATA  
-----

STABILITY: STABLE HAZARDOUS POLYMERIZATION WILL NOT OCCUR

CONDITIONS TO AVOID: Elevated temperatures

HAZARDOUS DECOMPOSITION PRODUCTS:

Burning may produce carbon dioxide and carbon monoxide.

INCOMPATIBILITY (MATERIALS TO AVOID): None reasonably foreseeable.

-----  
SECTION VII SPILL OR LEAK PROCEDURES  
-----

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Flush with water. Absorb with sawdust or rags.

WASTE DISPOSAL METHOD:

Conventional procedures in compliance with local, state and federal regulations. Do not incinerate sealed containers.

-----  
SECTION VIII SAFE HANDLING AND USE INFORMATION  
-----

RESPIRATORY PROTECTION:

Use NIOSH approved respirator specified for protection against paint spray mist and sanding dust in restricted or confined areas.

VENTILATION:

Adequate to maintain working atmosphere below T.L.V. and L.E.L.

(See Sect. II for ingredient data and concentrations). Mechanical exhaust may be required in confined areas.

PROTECTIVE GLOVES: Waterproof during repeated contact.

EYE PROTECTION : Splash goggles or safety glasses with side shields.

OTHER PROTECTIVE EQUIPMENT: Clothing adequate to protect skin.

HYGIENIC PRACTICES:

Remove and wash clothing before reuse. Wash hands before eating, smoking or using the washroom.

-----  
SECTION IX SPECIAL PRECAUTIONS  
-----

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Do not throw or drop containers.

OTHER PRECAUTIONS :

Avoid contact with eyes and prolonged contact with skin or breathing of

spray mist or sanding dust.  
Close container after each use. Keep out of reach of children. Do not  
take internally.

-----  
SECTION XX  
-----

HMIS (Hazardous Materials Identification System)(R) NPCA  
HMIS is a recognized workplace Hazard Communications System as required by  
OSHA (29 CFR 1910.1200). Information on establishing a compliant hazardous  
communication program using HMIS is available from:

American Labelmark Co., Inc., Labelmaster Division  
5724 N. Pulaski Rd., Chicago, IL 60646  
1-800-621-5808

The ratings assigned by Benjamin Moore & Co. are only suggested ratings;  
the contractor/employer has ultimate responsibility for HMIS rating where  
this system is used.

PERSONAL PROTECTION: This code is left blank on Benjamin Moore & Co. MSDS's  
as it depends on application technique and the workplace ventilation.

Please read Sections II through IX of this MSDS before deciding on  
appropriate protective equipment and beginning work. There are codes  
available for this section which can be obtained from Labelmaster.

Note: There are no SARA reportable materials in this product.

-----  
DISCLAIMER  
-----

The information contained herein is presented in good faith and believed  
to be accurate as of the effective date shown above. This information is  
furnished without warranty of any kind. Employers should use this  
information only as a supplement to other information gathered by them and  
must make independent determination of suitability and completeness of  
information from all sources to assure proper use of these materials and  
the safety and health of employees. Any use of this data and information  
must be determined by the user to be in accordance with applicable federal,  
state and local laws and regulations.

NOTICE: Removal of old paint by sanding, scraping or other means may  
generate dust or fumes which contain lead. Exposure to lead dust or fumes  
may cause adverse health effects, especially in children or pregnant women.  
Controlling exposure to lead or other hazardous substances requires the use  
of proper protective equipment, such as a properly fitted respirator (NIOSH  
approved) and proper containment and cleanup. For additional information,  
contact the USEPA/Lead Information Hotline at 1-800-LEAD-FYI.