KELLY-MOORE The Painter's Paint Store

SAFETY DATA SHEET

1. Identification

Product identifier 1610 AcryPlex Eggshell Interior Low VOC 100% Acrylic Enamel

Other means of identification

Product code 1610 (121, 222, 333, 555) **Architectural Coating** Recommended use

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Kelly-Moore Paint Co., Inc. Company name

Address 987 Commercial St.

San Carlos, CA 94070, USA

Email TAlvarez@kellymoore.com Tiffany Alvarez Gonda Contact person

Telephone 1-800-874-4436

CHEMTREC: 1-800-424-9300 **Emergency telephone**

2. Hazard(s) identification

Physical hazards Not classified.

Sensitization, skin **Health hazards** Category 1

> Carcinogenicity (inhalation) Category 2 Reproductive toxicity Category 2

Not classified. **OSHA** defined hazards

Label elements



Signal word

May cause an allergic skin reaction. May cause cancer by inhalation. Suspected of damaging **Hazard statement**

fertility or the unborn child.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Do not breathe dust. Contaminated work clothing must not be allowed out of the

workplace. Wear protective gloves/protective clothing/eye protection/face protection.

Response If on skin: Wash with plenty of water, If exposed or concerned: Get medical advice/attention, If

skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before

reuse.

Store locked up. **Storage**

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Titanium dioxide	13463-67-7	< 22
Kaolin	1332-58-7	< 5
Limestone	1317-65-3	< 5

SDS US

Chemical name	CAS number	%
Aluminum hydroxide	21645-51-2	< 2
Amorphous Silica: Uncalcinated Diatomaceous Earth	61790-53-2	< 2
Silicon dioxide, crystalline silica-free	7631-86-9	< 2
Trimethylolpropane	77-99-6	< 0.2
2-Methyl-2H-isothiazol-3-one	2682-20-4	< 0.1
3-lodo-2-propynyl butyl carbamate	55406-53-6	< 0.1
5-Chloro-2-methyl-2H-isothiazol-3-o ne	26172-55-4	< 0.1

All concentrations are in percent by weight (kg) unless ingredient is a gas. Gas concentrations are in percent by volume (I).

4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Symptoms may be delayed.

Most important Coughing. Discomfort in the chest. Shortness of breath. May cause an allergic skin reaction. symptoms/effects, acute and Dermatitis. Rash. Prolonged exposure may cause chronic effects.

symptoms/effects, acute and

delayed

Indication of immediate Provide general supportive measures and treat symptomatically. Keep victim under observation.

medical attention and special treatment needed

General information

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

modia

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters

Fire fighting

equipment/instructions

Specific methods
General fire hazards

None known.

During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Move containers from fire area if you can do so without risk. Use water spray to keep fire-exposed containers cool.

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in tightly closed original container in a dry, cool and well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

U.S OSHA Components	Туре	Value	
Silicon dioxide, crystalline	TWA	80 mg/m3	
silica-free (CAS 7631-86-9)		·	
JS. OSHA Table Z-1 Limits for Air Components	Contaminants (29 CFR 1910.1 Type	000) Value	Form
Kaolin (CAS 1332-58-7)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Limestone (CAS 1317-65-3)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Fitanium dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
JS. OSHA Table Z-3 (29 CFR 1910.			
Components	Туре	Value	Form
Amorphous Silica: Uncalcinated Diatomaceous Earth (CAS 61790-53-2)	TWA	0.8 mg/m3	
,		20 mppcf	
(aolin (CAS 1332-58-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
Silicon dioxide, crystalline silica-free (CAS 7631-86-9)	TWA	20 mppcf	
US. ACGIH Threshold Limit Values	;		
Components	Туре	Value	Form
Aluminum hydroxide (CAS 21645-51-2)	TWA	1 mg/m3	Respirable fraction.
(aolin (CAS 1332-58-7)	TWA	2 mg/m3	Respirable fraction.
Fitanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
US. NIOSH: Pocket Guide to Chem			_
Components	Туре	Value	Form
Amorphous Silica: Uncalcinated Diatomaceous Earth (CAS 61790-53-2)	REL	6 mg/m3	
	TWA	6 mg/m3	
(aolin (CAS 1332-58-7)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Limestone (CAS 1317-65-3)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Silicon dioxide, crystalline silica-free (CAS 7631-86-9)	TWA	6 mg/m3	

1610 AcryPlex Eggshell Interior Low VOC 100% Acrylic Enamel

SDS US

940925 Version #: 01 Revision date: - Issue date: 21-April-2021

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been

established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Skin protection

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to

dust/fume at levels exceeding the exposure limits.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance Milky white to colored liquid.

Physical stateLiquid.FormLiquid.ColorVarious.

Odor Slightly ammoniacal.

Odor threshold Not available.

pH 7 - 10

Melting point/freezing point Not available.

Initial boiling point and boiling Not available.

range

Flash point Not available.

Evaporation rate < 1 (n-BuAc=1)

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Poor pressure Not available.

Vapor pressureNot available.Vapor density> 1 (Air=1)Relative densityNot available.

Solubility(ies)

Solubility (water) Moderately soluble

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

VOC 1.75 - 2.82 g/L

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidizing agents. Strong acids.

Hazardous decomposition

products

Carbon oxides. Metal oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation Suspected of causing cancer by inhalation. Prolonged inhalation may be harmful.

Skin contact May cause an allergic skin reaction.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Components Species Test Results

Aluminum hydroxide (CAS 21645-51-2)

Acute Oral

LD50 Rat > 5000 mg/kg

Kaolin (CAS 1332-58-7)

Acute

Dermal

LD50 Rat > 5000 mg/kg

Inhalation

LC50 Rat > 2 mg/l, 4 Hours

Oral

LD50 Rat > 5000 mg/kg

Silicon dioxide, crystalline silica-free (CAS 7631-86-9)

Acute

Dermal

LD50 Rabbit > 5000 mg/kg, 24 Hours

Inhalation

Dust

LC50 Rat > 0.14 mg/l, 4 Hours

Oral

LD50 Rat > 3300 mg/kg

Titanium dioxide (CAS 13463-67-7)

Acute Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

1610 AcryPlex Eggshell Interior Low VOC 100% Acrylic Enamel 940925 Version #: 01 Revision date: - Issue date: 21-April-2021 Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Inhalation of titanium dioxide dust may cause cancer, however due to the physical form of the Carcinogenicity

product, inhalation of dust is not likely.

IARC Monographs. Overall Evaluation of Carcinogenicity

Amorphous Silica: Uncalcinated Diatomaceous Earth

(CAS 61790-53-2) Titanium dioxide (CAS 13463-67-7)

2B Possibly carcinogenic to humans.

3 Not classifiable as to carcinogenicity to humans.

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Suspected of damaging fertility or the unborn child. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Prolonged exposure may cause chronic effects. **Chronic effects**

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results	
Kaolin (CAS 1332-58-	7)			
Aquatic				
Acute				
Crustacea	LC50	Daphnia magna	> 1.1 g/l, 48 Hours	
Titanium dioxide (CAS	3 13463-67-7)			

Aquatic

Acute

Crustacea EC50 Daphnia magna > 100 mg/l, 48 Hours Fish LL50 Oryzias latipes > 100 mg/l, 96 Hours

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

No data available.

Mobility in soil

The product is water soluble and may spread in water systems.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of **Disposal instructions**

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

1610 AcryPlex Eggshell Interior Low VOC 100% Acrylic Enamel 940925 Version #: 01 Revision date: - Issue date: 21-April-2021

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to No.

Not established.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

2-Methyl-2H-isothiazol-3-one (CAS 2682-20-4) 1.0 % One-Time Export Notification only.

5-Chloro-2-methyl-2H-isothiazol-3-one 1.0 % One-Time Export Notification only.

(CAS 26172-55-4)

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Toxic Substances Control Act (TSCA)

All components on the TSCA 8(b) inventory are designated "active" or are

exempt from reporting under the Inventory Update Rule.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

Classified hazard

Respiratory or skin sensitization

categories

Carcinogenicity
Reproductive toxicity

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Contains component(s) regulated under the Safe Drinking Water Act.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Amorphous Silica: Uncalcinated Diatomaceous Earth (CAS 61790-53-2)

Kaolin (CAS 1332-58-7)

Limestone (CAS 1317-65-3)

Silicon dioxide, crystalline silica-free (CAS 7631-86-9)

Titanium dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

3-lodo-2-propynyl butyl carbamate (CAS 55406-53-6)

Amorphous Silica: Uncalcinated Diatomaceous Earth (CAS 61790-53-2)

Kaolin (CAS 1332-58-7)

Limestone (CAS 1317-65-3)

Titanium dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Amorphous Silica: Uncalcinated Diatomaceous Earth (CAS 61790-53-2)

Kaolin (CAS 1332-58-7) Limestone (CAS 1317-65-3)

Silicon dioxide, crystalline silica-free (CAS 7631-86-9)

Titanium dioxide (CAS 13463-67-7)

US. Rhode Island RTK

Amorphous Silica: Uncalcinated Diatomaceous Earth (CAS 61790-53-2)

Kaolin (CAS 1332-58-7) Limestone (CAS 1317-65-3) Titanium dioxide (CAS 13463-67-7)

California Proposition 65



WARNING: This product can expose you to chemicals including Ethylene oxide, which is known to the State of

California to cause cancer and birth defects or other reproductive harm. For more information go

to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

1,4-Dioxane (CAS 123-91-1)Listed: January 1, 1988Acetaldehyde (CAS 75-07-0)Listed: April 1, 1988Ethylene oxide (CAS 75-21-8)Listed: July 1, 1987Formaldehyde (CAS 50-00-0)Listed: January 1, 1988Methyloxirane (CAS 75-56-9)Listed: October 1, 1988Silica, Crystalline (airborne particles of respirableListed: October 1, 1988

size) (CAS 14808-60-7)

Titanium dioxide (CAS 13463-67-7) Listed: September 2, 2011

California Proposition 65 - CRT: Listed date/Developmental toxin

Ethylene oxide (CAS 75-21-8) Listed: August 7, 2009

California Proposition 65 - CRT: Listed date/Female reproductive toxin

Ethylene oxide (CAS 75-21-8) Listed: February 27, 1987

California Proposition 65 - CRT: Listed date/Male reproductive toxin

Ethylene oxide (CAS 75-21-8) Listed: August 7, 2009

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Titanium dioxide (CAS 13463-67-7)

International Inventories

Country(s) or region Inventory name
United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

On inventory (yes/no)*

Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 21-April-2021

Revision date - 01

HMIS® ratings Health: 2*

Flammability: 1 Physical hazard: 0

Disclaimer Kelly-Moore Paint Co., Inc. cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently

available.

940925 Version #: 01 Revision date: - Issue date: 21-April-2021