# KELLY-MOORE\* PAINTS The Painter's Paint Store

# SAFETY DATA SHEET

## 1. Identification

Product identifier 1247 AcryShield Exterior Satin

Other means of identification

**Product code** 1247 (121, 222, 333, 555), 1247-1, 1247-3, 1247-5

Recommended use Architectural Coating

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

**Company name** Kelly-Moore Paint Co., Inc.

Address 1390 El Camino Real, Third Floor

San Carlos, CA 94070, USA

Email TAlvarez@kellymoore.com

**Contact person** Tiffany Alvarez Gonda **Telephone** 1-800-874-4436

Emergency telephone CHEMTREC: 1-800-424-9300

# 2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Sensitization, skin Category 1

Carcinogenicity (inhalation) Category 2
Reproductive toxicity Category 2

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement May cause an allergic skin reaction. Suspected of causing cancer by inhalation. Suspected of

damaging fertility or the unborn child.

**Precautionary statement** 

**Prevention** Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Do not breathe dust. Contaminated work clothing must not be allowed out of the

workplace. Wear protective gloves/protective clothing/eye protection/face protection.

Response If on skin: Wash with plenty of water. If exposed or concerned: Get medical advice/attention. If

skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before

reuse.

Storage Store locked up.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

## 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	CAS number	%
Titanium dioxide	13463-67-7	< 20
Diphenyl ketone	119-61-9	< 0.2
Trimethylolpropane	77-99-6	< 0.2

1247 AcryShield Exterior Satin SDS US

929997 Version #: 02 Revision date: 06-May-2022 Issue date: 29-September-2021

Chemical name	CAS number	%
2-Methyl-2H-isothiazol-3-one	2682-20-4	< 0.1
5-Chloro-2-methyl-2H-isothiazol-3-o	26172-55-4	< 0.1

All concentrations are in percent by weight (kg) unless ingredient is a gas. Gas concentrations are in percent by volume (I).

#### 4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

Call a physician if symptoms develop or persist.

Remove contaminated clothing immediately and wash skin with soap and water. In case of Skin contact

eczema or other skin disorders: Seek medical attention and take along these instructions.

Rinse with water. Get medical attention if irritation develops and persists. Eve contact

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic

effects.

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

**General information** 

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

# 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

None known.

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters

During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace.

Fire fighting equipment/instructions

Specific methods General fire hazards Move containers from fire area if you can do so without risk. Use water spray to keep fire-exposed containers cool.

Use standard firefighting procedures and consider the hazards of other involved materials. No unusual fire or explosion hazards noted.

# 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing dust. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

**Environmental precautions** 

Avoid discharge into drains, water courses or onto the ground.

# 7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

1247 AcryShield Exterior Satin SDS US Store in tightly closed original container in a dry, cool and well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

#### Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

ComponentsTypeValueFormTitanium dioxide (CAS 13463-67-7)PEL15 mg/m3Total dust.

**US. ACGIH Threshold Limit Values** 

ComponentsTypeValueTitanium dioxide (CAS 13463-67-7)TWA 10 mg/m3

US. Workplace Environmental Exposure Level (WEEL) Guides

ComponentsTypeValueDiphenyl ketone (CAS 119-61-9)TWA 0.5 mg/m3

**Biological limit values** 

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

Skin protection

**Hand protection** Wear appropriate chemical resistant gloves.

Skin protection

Other Wear appropriate chemical resistant clothing.

**Respiratory protection** When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to

dust/fume at levels exceeding the exposure limits.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

#### 9. Physical and chemical properties

Appearance Milky white to colored liquid.

Physical stateLiquid.FormLiquid.ColorVarious.

Odor Slightly ammoniacal.

Odor threshold Not available.

**pH** 7 - 10

Melting point/freezing point Not available.

Initial boiling point and boiling Not available.

range

Flash point

Evaporation rate

Volume 1 (n-BuAc=1)

Flammability (solid, gas)

Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

1247 AcryShield Exterior Satin SDS US

929997 Version #: 02 Revision date: 06-May-2022 Issue date: 29-September-2021

Not available. Vapor pressure > 1 (Air=1)Vapor density Relative density Not available.

Solubility(ies)

Solubility (water) Moderately soluble **Partition coefficient** 

(n-octanol/water)

Not available.

Not available. **Auto-ignition temperature Decomposition temperature** Not available. **Viscosity** Not available.

Other information

**Explosive properties** Not explosive. **Oxidizing properties** Not oxidizing. VOC 45.085 - 45.911 g/L

# 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials. Incompatible materials Strong oxidizing agents. Strong acids.

**Hazardous decomposition** 

products

Carbon oxides. Metal oxides.

## 11. Toxicological information

#### Information on likely routes of exposure

Inhalation Suspected of causing cancer by inhalation. Prolonged inhalation may be harmful.

Skin contact May cause an allergic skin reaction.

Eye contact Direct contact with eyes may cause temporary irritation.

May cause discomfort if swallowed. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics May cause an allergic skin reaction. Dermatitis. Rash.

#### Information on toxicological effects

**Acute toxicity** Not expected to be acutely toxic.

Components **Species Test Results** 

Titanium dioxide (CAS 13463-67-7)

**Acute** Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. Serious eve damage/eve Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer by inhalation.

#### IARC Monographs. Overall Evaluation of Carcinogenicity

Diphenyl ketone (CAS 119-61-9) 2B Possibly carcinogenic to humans. Titanium dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans

1247 AcryShield Exterior Satin SDS US

Issue date: 29-September-2021 929997 Version #: 02 Revision date: 06-May-2022

## **NTP Report on Carcinogens**

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Suspected of damaging fertility or the unborn child. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** Not an aspiration hazard.

**Chronic effects** Prolonged exposure may cause chronic effects.

## 12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity** 

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components **Species Test Results** 

Diphenyl ketone (CAS 119-61-9)

Aquatic Acute

Crustacea EC50 Water flea (Daphnia magna) >= 0.21 - <= 0.37 mg/l, 24 hours

Fish Fathead minnow (Pimephales promelas) >= 13.2 - <= 15.3 mg/l, 96 hours LC50

>= 5.96 - <= 7.41 mg/l, 7 days

Titanium dioxide (CAS 13463-67-7)

Aquatic

Acute

EC50 Daphnia magna > 100 mg/l, 48 Hours Crustacea LL50 Fish Oryzias latipes > 100 mg/l, 96 Hours

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

No data available.

Mobility in soil

The product is water soluble and may spread in water systems.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

#### 13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

#### 14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not established.

the IBC Code

1247 AcryShield Exterior Satin

Issue date: 29-September-2021 929997 Version #: 02 Revision date: 06-May-2022

5/7

## 15. Regulatory information

**US** federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

2-Methyl-2H-isothiazol-3-one (CAS 2682-20-4) 1.0 % One-Time Export Notification only. 5-Chloro-2-methyl-2H-isothiazol-3-one 1.0 % One-Time Export Notification only.

(CAS 26172-55-4)

Diphenyl ketone (CAS 119-61-9) 0.1 % One-Time Export Notification only.

#### CERCLA Hazardous Substance List (40 CFR 302.4)

#### SARA 304 Emergency release notification

Not regulated.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

**Toxic Substances Control Act (TSCA)** 

All components on the TSCA 8(b) inventory are designated "active" or are

exempt from reporting under the Inventory Update Rule.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

Yes

#### SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

Classified hazard categories

Respiratory or skin sensitization

Carcinogenicity

Reproductive toxicity

## SARA 313 (TRI reporting)

Not regulated.

## Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

## Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

## US state regulations

#### **US. Massachusetts RTK - Substance List**

Titanium dioxide (CAS 13463-67-7)

#### **US. New Jersey Worker and Community Right-to-Know Act**

Titanium dioxide (CAS 13463-67-7)

#### US. Pennsylvania Worker and Community Right-to-Know Law

Titanium dioxide (CAS 13463-67-7)

#### **US. Rhode Island RTK**

Titanium dioxide (CAS 13463-67-7)

# **California Proposition 65**



WARNING: This product can expose you to chemicals including Ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go

to www.P65Warnings.ca.gov.

# California Proposition 65 - CRT: Listed date/Carcinogenic substance

1,4-Dioxane (CAS 123-91-1) Listed: January 1, 1988 Acetaldehyde (CAS 75-07-0) Listed: April 1, 1988 Listed: February 27, 1987 Benzene (CAS 71-43-2) Cumene (CAS 98-82-8) Listed: April 6, 2010 Dichloromethane (CAS 75-09-2) Listed: April 1, 1988 Diphenyl ketone (CAS 119-61-9) Listed: June 22, 2012 Ethylbenzene (CAS 100-41-4) Listed: June 11, 2004 Listed: July 1, 1987 Ethylene oxide (CAS 75-21-8) Formaldehyde (CAS 50-00-0) Listed: January 1, 1988 Methyloxirane (CAS 75-56-9) Listed: October 1, 1988

SDS US 1247 AcryShield Exterior Satin

929997 Version #: 02 Revision date: 06-May-2022 Issue date: 29-September-2021 Titanium dioxide (CAS 13463-67-7) Listed: September 2, 2011

## California Proposition 65 - CRT: Listed date/Developmental toxin

 Benzene (CAS 71-43-2)
 Listed: December 26, 1997

 Ethylene oxide (CAS 75-21-8)
 Listed: August 7, 2009

 Methanol (CAS 67-56-1)
 Listed: March 16, 2012

 Toluene (CAS 108-88-3)
 Listed: January 1, 1991

#### California Proposition 65 - CRT: Listed date/Female reproductive toxin

Ethylene oxide (CAS 75-21-8) Listed: February 27, 1987

## California Proposition 65 - CRT: Listed date/Male reproductive toxin

Benzene (CAS 71-43-2)
Ethylene oxide (CAS 75-21-8)
Listed: December 26, 1997
Listed: August 7, 2009

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Diphenyl ketone (CAS 119-61-9) Titanium dioxide (CAS 13463-67-7)

## 16. Other information, including date of preparation or last revision

**Issue date** 29-September-2021

Revision date 06-May-2022

Version # 02

**HMIS® ratings** Health: 2\*

Flammability: 1 Physical hazard: 0

**Disclaimer** Kelly-Moore Paint Co., Inc. cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently

available.

1247 AcryShield Exterior Satin SDS US