



# EXTERIOR

# PRODUCT DATA SHEET

## PRODUCT

### Select Paint/Primer In One Exterior Flat Finish

## DESCRIPTION

A durable 100% acrylic latex flat house paint with a Lifetime warranty when applied according to all label directions on a properly prepared surface.

## COLORS

Pastel Base  
Deep Base  
Tint Base  
Neutral Base

## SURFACE PREP

See "Surface Prep" section for recommendations.

## APPLICATION

This paint can be used over latex or oil-based paint. Inter-mix all containers for color uniformity. Stir thoroughly before and during use. Certain colors may require more than one coat. Do not apply over a surface that has not been properly prepared. Do not apply if rain or dew is expected within 24 hrs. or if outside temperature could drop below 40°. Use product when surface and air temperature are between 50-90°. Do not apply in hot sun; follow shade around house. Do not over spread. Use a premium brush or pad applicator. If spray applied back brushing is recommended to assure adequate penetration into the substrate. For best performance; apply two coats on new surfaces after priming. Allow new masonry to cure at least 30 days before coating

## RECOMMENDED USES

Exterior new, weathered or previously painted surfaces such as masonry, stucco, concrete block, brick and concrete. May also be used on properly prepared wood, factory primed siding and cement board.

## ENVIRONMENTAL VARIABLES

Thin sparingly with water if necessary for spraying. Dries in 1-2 hours. Allow to dry overnight before recoating. High humidity or low temperature may increase dry time. After 2-4 weeks, cured paint may be cleaned with a mild, non-abrasive liquid detergent. Dry Paint film is mildew resistant. Coverage of 400 sq. per gallon depending on the porosity of the surface to be painted.

## CLEAN-UP

Wash tools with warm water and soap immediately after applying. Properly dispose of all soiled rags.

## CAUTIONS

Do not expose this container to excessive heat. Close container after each use. Keep from freezing.

Disposal - Full: Give remaining product to neighbors or community organization. Partially full: (If state or local regulations allow) Pour residue into absorbent material. When dry, dispose of in trash for pick up. Empty: This container may be accepted in a recycling program. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

## PHYSICAL PROPERTIES

Resin Type	Acrylic Latex
Dry Time at 60°	2-6
Weight per gallon	10.6 lbs. + .2
Percent solids by weight	49.4 + 2%
Percent solids by volume	37.0 + 2%
Viscosity Range	95-105 KU
VOC	Less than 50 g/l 0.84 lbs./gal.

Revised: 05/2023

AXIOS Coating Group  
148 Lower Main Street  
Aberdeen, NJ 07747

### Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since GPM does not control the application of its products, or the condition of the surfaces to which they are applied, AXIOS' liability will under no circumstances exceed replacement of the product.



# EXTERIOR

# PRODUCT DATA SHEET

## PRODUCT

### Select Paint/Primer In One Exterior Satin Finish

## DESCRIPTION

High quality exterior 100% acrylic latex satin finish house & trim paint with a Lifetime warranty when applied according to all label directions on a properly prepared surface.

## COLORS

- Pastel Base
- Deep Base
- Tint Base
- Neutral Base

## SURFACE PREP

See "Surface Prep" section for recommendations.

## APPLICATION

This paint can be used over latex or oil-based paint. Inter-mix all containers for color uniformity. Stir thoroughly before and during use. Certain colors may require more than one coat. Do not apply over a surface that has not been properly prepared. Do not apply if rain or dew is expected within 24 hrs. or if outside temperature could drop below 40°. Use product when surface and air temperature are between 50-90°. Do not apply in hot sun; follow shade around house. Do not over spread. Use a premium brush or pad applicator. If spray applied back brushing is recommended to assure adequate penetration into the substrate. For best performance; apply two coats on new surfaces after priming. Allow new masonry to cure at least 30 days before coating

## RECOMMENDED USES

Exterior new, weathered or previously painted surfaces such as masonry, stucco, concrete block, brick and concrete. May also be used on properly prepared wood and factory primed siding.

## ENVIRONMENTAL VARIABLES

Thin sparingly with water if necessary for spraying. Dries in 1-2 hours. Allow to dry overnight before recoating. High humidity or low temperature may increase dry time. After 2-4 weeks, cured paint may be cleaned with a mild, non-abrasive liquid detergent. Dry Paint film is mildew resistant. Coverage of 400 sq. per gallon depending on the porosity of the surface to be painted.

## CLEAN-UP

Wash tools with warm water and soap immediately after applying. Properly dispose of all soiled rags.

## CAUTIONS

Do not expose this container to excessive heat. Close container after each use. Keep from freezing.

Disposal - Full: Give remaining product to neighbors or community organization. Partially full: (If state or local regulations allow) Pour residue into absorbent material. When dry, dispose of in trash for pick up. Empty: This container may be accepted in a recycling program. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

## PHYSICAL PROPERTIES

Resin Type	Acrylic Latex
Dry Time at 60°	10-20
Weight per gallon	10.2 lbs. + .2
Percent solids by weight	46.7% + 2%
Percent solids by volume	36.6% + 2%
Viscosity Range	75-105 KU
VOC	Less than 50 g/l 0.42 lbs./gal.
MPI Certification	15

Revised: 05/2023

AXIOS Coating Group  
148 Lower Main Street  
Aberdeen, NJ 07747

### Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since GPM does not control the application of its products, or the condition of the surfaces to which they are applied, AXIOS' liability will under no circumstances exceed replacement of the product.

## PRODUCT

### Select Paint/Primer In One Exterior Semi-Gloss Finish

## DESCRIPTION

High quality exterior 100% acrylic latex semi-gloss house & trim finish with a Lifetime warranty when applied according to all label directions on a properly prepared surface.

## COLORS

Pastel Base  
Deep Base  
Tint Base  
Neutral Base

## SURFACE PREP

See "Surface Prep" section for recommendations.

## APPLICATION

This paint can be used over latex or oil-based paint. Inter-mix all containers for color uniformity. Stir thoroughly before and during use. Certain colors may require more than one coat. Do not apply over a surface that has not been properly prepared. Do not apply if rain or dew is expected within 24 hrs. or if outside temperature could drop below 40°. Use product when surface and air temperature are between 50-90°. Do not apply in hot sun; follow shade around house. Do not over spread. Use a premium brush or pad applicator. If spray applied back brushing is recommended to assure adequate penetration into the substrate. For best performance; apply two coats on new surfaces after priming. Allow new masonry to cure at least 30 days before coating

## RECOMMENDED USES

Previously painted or primed exterior surfaces, including properly prepared wood, vinyl, aluminum and factory primed siding, This product is Master Painter Institute certified and approved for use by the United States Government.

## ENVIRONMENTAL VARIABLES

Thin sparingly with water if necessary for spraying. Dries in 1-2 hours. Allow to dry overnight before recoating. High humidity or low temperature may increase dry time. After 2-4 weeks, cured paint may be cleaned with a mild, non-abrasive liquid detergent. Dry Paint film is mildew resistant. Coverage of 400 sq. per gallon depending on the porosity of the surface to be painted.

## CLEAN-UP

Wash tools with warm water and soap immediately after applying. Properly dispose of all soiled rags.

## CAUTIONS

Do not expose this container to excessive heat. Close container after each use. Keep from freezing.

Disposal - Full: Give remaining product to neighbors or community organization. Partially full: (If state or local regulations allow) Pour residue into absorbent material. When dry, dispose of in trash for pick up. Empty: This container may be accepted in a recycling program. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

## PHYSICAL PROPERTIES

Resin Type	Acrylic Latex
Dry Time at 60°	45-55
Weight per gallon	9.7 lbs. + .2
Percent solids by weight	41.0% + 2%
Percent solids by volume	33.0% + 2%
Viscosity Range	95-105 KU
VOC	Less than 50 g/l 0.42 lbs./gal.
MPI Certification	11

Revised: 05/2023

### Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since GPM does not control the application of its products, or the condition of the surfaces to which they are applied, AXIOS' liability will under no circumstances exceed replacement of the product.